

STRØMAGGREGATER RENTAL COMPACT

16kVA-550kVA



VARIANTER	R16CC	R22C3	R33C3	R44C3	R66C3	R90C3	R110C3	R135C3	R165C3	R220C3	R275C3	R330C3	R450C3	R550C3
PRP power (kVA)	15	20	30	40	60	82	100	123	150	200	250	300	400	500
PRP power (kW)	12	16	24	32	48	66	80	98	120	160	200	240	320	400
ESP power (kVA)	16	22	33	40	66	90	110	135	165	220	275	330	440	550
ESP power (kW)	13	18	26	32	53	72	88	108	132	176	220	264	352	440
Nominell strøm (A)	23	32	48	58	95	130	159	195	238	318	397	476	635	794
Lydtrykk @ 1m i dB(A)	71	74	72	71	77	75	75	77	78	78	77	78	75	76
Lydtrykk 2 7m i dB(A)	61	60	60	59	66	64	64	66	68	68	66	67	65	66
Lydnivå (Lwa)	87	60	90	88	95	93	93	95	96	96	97	97	95	96
GENERATOR														
Fabrikkat	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer
Modell	LSA40S3	LSA40M5	LSA423VS3	LSA423S5	LSA423L9	LSA432L8	LSA442VS45	LSA442S7	LSA442M95	LSA462M5	LSA462L6	LSA462VL12	LSA472VS3	LSA472M7
MOTOR /1500 RPM														
Fabrikkat	MITSUBISHI	MITSUBISHI	MITSUBISHI	MITSUBISHI	JOHN DEERE	JOHN DEERE	JOHN DEERE	JOHN DEERE	JOHN DEERE	JOHN DEERE	JOHN DEERE	JOHN DEERE	VOLVO	VOLVO
Modell	S4L2-6ISD	S4Q2+Z361SD	S4S- Z361SD	S4S- Z3DT61SD	4045HFS85	4045HFS86	4045HFS87	4045HFS88	6068HFS85	6068HFS86	6090HFS85	6090HFS86	TAD1355GE	TAD1651GE
Prime output (kW)	14,4	20,3	28,3	36	55,0	75,4	93,4	112,2	139	184	230,4	276,6	369	441
Ant. sylinder	4	4	4	4	4	4	4	4	6	6	6	6	6	6
V	12	12	12	12	12	12	12	12	12	12	12	12	24	24
Kapasitet (l)	1,76	2,51	3,33	3,33	4,48	4,48	4,48	4,48	6,72	6,72	8,98	8,98	12,78	16,12
Forbruk v/ 75% last	3,4	4,8	6,2	8,1	12,7	15,2	20,7	20,7	24,5	37,6	43,2	50,7	66,7	79,8
Drivstoff/ Avkjøling	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann	Diesel/Vann
HCNOx utslipp @ ESP (g/kWh)	Ikke påvirket	7,4	7,4	7,4	4,16	3,54	3,54	3,54	3,68	3,68	3,89	3,89	3,61	3,62
DRIVSTOFFTANK														
Maks.kapasitet (L)	153	153	220	220	390	527	527	527	860	860	1083	1083	1481	1481
Min. kapasitet tank (L)	x	X	X	X	X	209	209	209	377	377	X	X	X	X
DRIFTSTID DOBBELTVEGGET KAPASITET (TIMER)														
ved 100% last	34,8	24,7	25,6	21,2	26,4	26,6	21,7	18,6	24,6	18,7	18,9	15,8	17,8	14,5
ved 75% last	45	31,9	35,5	27,2	30,7	34,7/13,8*	25,5/10,1*	22,9/9,1*	35,1/15,4*	22,9/10*	25,1	21,4	22,2	18,6
ved 50% last	58,8	45	51,1	49,4	41,9	46,6	36,9	31,4	47,8	33	34,8	29,6	30,7	26,9
DIMENSJONER MED DOBBELTVEGGET DRIVSTOFFTANK														
	M3126		M3127		M3128	M3129			M3226		M3227		M3228	
Lengde (mm)	1850	1850	2200	2200	2545	2860	2860	2860	3520	3520	4332	4332	5000	5000
Bredde (mm)	901	901	1000	1000	1150	1191	1191	1191	1190	1190	1361	1361	1611	1611
Høyde (mm)	1355	1355	1528	1528	1824	1850*	1850*	1850*	1920*	1920*	2431	2431	2600	2600
Vekt (kg)	900	937	1277	1312	2040	2045	2620	2165*	2792*	2922*	5060	5180	6855	7476