

| References | | | | |
|--|----------|----------|---------------|--------------|
| Screw terminal connection sockets 16A/250V | | | | |
| Description | Ref. | | Colour | Illustration |
| | Schuko | French | | |
| Socket with protective shutter | K01/6 | K02/6 | Red | |
| | K01/7 | K02/7 | Orange | |
| | K01/9 | K02/9 | Pure white | |
| | K01/14 | K02/14 | Graphite grey | |
| Socket with safety shutter and pilot Light (including pin) | KLS01/6 | KLS02/6 | Red | |
| | KLS01/7 | KLS02/7 | Orange | |
| | KLS01/9 | KLS02/9 | Pure white | |
| | KLS01/14 | KLS02/14 | Graphite grey | |
| Socket with protective shutter and pilot light | KL01/6 | KL02/6 | Red | |
| | KL01/7 | KL02/7 | Orange | |
| | KL01/9 | KL02/9 | Pure white | |
| | KL01/14 | KL02/14 | Graphite grey | |

| References | | | | |
|--|---------|---------|---------------|--------------|
| Quick terminal connection sockets 16A/250V | | | | |
| Description | Ref. | | Colour | Illustration |
| | Schuko | French | | |
| Socket with protective shutter | K11/6 | K22/6 | Red | |
| | K11/7 | K22/7 | Orange | |
| | K11/9 | K22/9 | Pure white | |
| | K11/14 | K22/14 | Graphite grey | |
| Socket with safety shutter (including pin) | KS11/6 | KS22/6 | Red | |
| | KS11/7 | KS22/7 | Orange | |
| | KS11/9 | KS22/9 | Pure white | |
| | KS11/14 | KS12/14 | Graphite grey | |
| Connection block for multi-sockets | AC11 | | - | |
| Spare | AC33/6 | | Red | |

2. K45 PLATES FOR PROTECTION ELEMENTS

Technical specifications:

- Plate sizes: 45 x 135 mm for elements with DIN and 45 x 45 mm format for protection elements.
- Electrical specifications of sockets: 16A/250V
- IP20

Standards:

- Automatic circuit breakers and differentials designed in compliance with Spanish standard UNE 20315 (Schuko sockets) and French standard NF C 61-303 (French sockets).

Manufacturing material:

- Halogen-free, fireproof thermoplastic.
- Guarantees non-spreading of flames in the case of fire and low toxicity in the case of smoke emissions due to no halogen content.

| References | | | | |
|--|-----------|---------------|--------------|--|
| Protection elements | | | | |
| K45 plate mechanisms for DIN elements | | | | |
| Description | Ref. | Colour | Illustration | |
| K45 plate mechanisms with 16A bipolar circuit-breaker, curve C | KF04A/9 | Pure white | | |
| | KF04A/14 | Graphite grey | | |
| K45 plate mechanisms with 10A bipolar circuit-breaker, curve C | KF104B/9 | Pure white | | |
| | KF104B/14 | Graphite grey | | |
| K45 plate with 25A differential with sensitivity of 30 mA | KF04C/9 | Pure white | | |
| | KF04C/14 | Graphite grey | | |
| K45 plates for automatic breaker or differential, DIN format | KF03/9 | Pure white | | |
| | KF03/14 | Graphite grey | | |

| References | | | | |
|--|----------|---------------|--------------|--|
| Protection elements | | | | |
| K45 plate with protection element | | | | |
| Description | Ref. | Colour | Illustration | |
| K45 plate with 10A automatic circuit-breaker, curve C | K106A/9 | Pure white | | |
| | K106A/14 | Graphite grey | | |
| K45 plate with 10A circuit-breaker differential with sensitivity of 10mA | K107A/9 | Pure white | | |
| | K107A/14 | Graphite grey | | |