



LED TECHNOLOGY

3000 sqm
Illuminated area

Leader in sustainability 

BATTERY Line



Operation: **100% BATTERY**
Power Battery Pack
24Vdc 400Ah (36H)
24Vdc 800Ah (72H)

X-ECO
BATTERY


4x100W LED- 8,5M
36H-72H

T-ZERO PRO

X-ECO BATTERY



4x100W LED- 8,5M
36H-72H

T-ZERO PRO



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Standard timer for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 14 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 110 km/h
- 4 height adjustable stabilizers
- On board levels for guidance during stabilization
- **Running time 36-72h**
- 24 Vdc Battery
- Floodlights 4x100W
- **Recharging in 8 hours**
- 230V 1PH built-in Battery charger



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)	
		2540x1390x2420(LxWxH)		2540x1550x8500 (LxWxH)		910 (36H) - 1242 (72H)
Floodlights	Type	Power (each)	Floodlights number	IP level	Timer	Illuminated area (sqm)
	Led	100W	4	65	Built-in	3000
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Safety valve to raise down the mast	
	Hydraulic	8,5 m	110 km/h	340°	yes	
Battery	Type	Power Battery Pack	Running time	Expected battery cycle	Expected battery life time	Charging time with floodlights off
	AGM	24Vdc 400Ah - (36H) 24Vdc 800Ah - (72H)	36 h - 72 h	500	18000 h	8 h
Factory options	Running time					
	300 h dimmable configuration					



TRIME® Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it
Lighting Towers